

TM2000 Absolute efficiency in harvesting applications











HIGH LOAD CAPACITY

EXTENDED TIRE LIFE

LATERAL STABILITY

PREMIUM TRACTION

Built to perform in harvesting applications, the TM2000 radial tire offers superior traction across all terrains.

Its durable construction handles heavy loads without compromise, while the self-cleaning tread pattern ensures optimal uptime and productivity.



Delivers maximum reliability in the most demanding working conditions, even when carrying high loads, thanks to the robust radial construction, which also guarantees high lateral stability on hilly terrain.



Excellent self-cleaning thanks to interlug terraces.





Lug footprint comparison - Index Higher is better

100



TM2000

+21%

vs. Premium Competitor





Premium Competitor

Size	Tread Pattern	SW mm	OD mm	SLR mm	RC mm	SRI	Rim	Permitted Rims	Туре	Tube
620/75R26 166A8 (23.1R26)	TM2000	633	1590	716	4850	750	DW20B		TUBELESS	
650/75R32 172A8 (24.5R32)	TM2000	662	1817	805	5495	850	DW20B		TUBELESS	24.5-32
710/75R32 177A8	TM2000	735	1850	830	5595	850	DW23B	DW21B	TUBELESS	30.5-32
800/65R32 178A8 (30.5LR32)	TM2000	800	1846	829	5595	875	DW27B	DW25B - DH27 - DW28B	TUBELESS	30.5-32
900/60R32 181A8	TM2000	890	1900	855	5765	900	DW30B	DW27B - DW28B	TUBELESS	30.5-32



Yokohama TWS S.p.A.

Via Nazionale Tiburtina, 143 - 00019 Villa Adriana - Tivoli (RM), Italy Phone: +39 0774 3841 - info.tws@yokohama-tws.com

www.trelleborg-tires.com









