



T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

Polymer Engineering, Application Expertise

As part of our premium range this product is capable of performing in demanding applications to deliver high performance in key areas.



TIRE LIFE



PUNCTURE RESISTANCE



COOL RUNNING



STABILITY

MAIN BENEFITS

Block tread design

Large footprint lowers stress and maximizes tire life.

Sidewall protection

Reinforced sidewall to avoid impact damage.

Enhanced stability

Faster load positioning and cornering.

Wear resistant technology

Maximum lifetime, reduced downtime, increasing value.

Energy management system

Keeps the internal temperature low ensuring maximum uptime.

Shock absorbance

Tire absorbs shock from obstacles.

Rim security

Rim protection from accidental damage and anti slip bead wires.

T-900

BIAS PNEUMATIC - MAXIMUM INTENSITY APPLICATIONS

Tread pattern



T-900

Size	Alternative Size	Ply Rating	Rim	Product Dimensions			Minimal Dual Spacing [inch]	Inflation Pressure [psi]	Tire Type	Load Index	Speed Symbol	Load Capacity [lbs]	
				Overall Diameter [inch]	Section Width [inch]	Tread Depth [32 nd]						Counterbalanced lift trucks up to 16 mph	
												Load Wheel	Steering Wheel
5.00-8		10	3.00D-8	18.4	5.5	16	6.2	145	Tube Type	111	A5	3,120	2,403
18x7-8	180/70-8	16	4.33R-8	18.2	6.6	20	7.8	145	Tube Type	125	A5	4,729	3,638
6.00-9		12	4.00E-09	21.4	6.3	19	7.6	145	Tube Type	121	A5	4,156	3,197
23x9-10	225/75-10	20	6.50F-10	23.0	9.1	23	10.2	145	Tube Type	142	A5	7,595	5,842
6.50-10		12	5.00F-10	23.2	7.2	23	8.3	131	Tube Type	125	A5	4,729	3,638
23x10-12	250/60-12	20	8.00G-12	23.6	9.6	28	11.5	145	Tube Type	145	A5	8,311	6,393
7.00-12		14	5.00S-12	26.8	7.5	23	9.1	131	Tube Type	134	A5	6,074	4,674
7.00-12		16	5.00S-12	26.8	7.5	23	9.1	145	Tube Type	136	A5	6,415	4,938
27x10-12	250/75-12	16	8.00G-12	27.0	9.8	28	11.5	116	Tube Type	146	A5	8,598	6,614
27x10-12	250/75-12	24	8.00G-12	27.0	9.8	28	11.5	151	Tube Type	155	A5	11,111	8,543
28x9-15	225/75-15 (8.15-15)	14	7.0-15	28.0	9.1	23	9.8	145	Tube Type	146	A5	8,598	6,614
250-15	250/70-15	20	7.0-15	29.2	9.4	23	11.1	145	Tube Type	155	A5	11,111	8,543
7.00-15	29x8-15	14	5.5-15	29.9	8.0	25	9.3	128	Tube Type	140	A5	7,220	5,556
7.50-15		16	6.0-15	30.6	8.5	26	10.0	145	Tube Type	146	A5	8,598	6,614
7.50-16	250/80-16	12	6.00G-16	31.7	8.7	26	10.0	116	Tube Type	144	A5	8,003	6,151
300-15	315/70-15	20	8.0-15	33.1	11.4	28	13.6	131	Tube Type	164	A5	14,33	11,023
8.25-15		14	6.5-15	33.1	9.7	23	11.1	116	Tube Type	149	A5	9,315	7,165
8.25-15		16	6.5-15	33.1	9.7	23	11.1	135	Tube Type	152	A5	10,174	7,826
355/65-15	32x12½-15 (350-15)	24	9.75-15	33.2	13.1	36	16.0	145	Tube Type	170	A5	17,196	13,228
355/65-15	32x12½-15 (350-15)	32*	9.75-15	33.2	13.1	36	16.0	181	Tube Type	177	A5	20,922	16,094
9.00-20	270/95-20	14	7.0-20	40.0	10.4	34	12.2	131	Tube Type	160	A5	12,897	9,921
10.00-20	290/95-20	16	7.5-20	42.7	11.6	40	13.1	131	Tube Type	164	A5	14,33	11,023
11.00-20	300/95-20	18	8.0-20	43.7	11.9	42	13.9	145	Tube Type	170	A5	17,196	13,228
12.00-20	330/95-20	20	8.0-20	45.1	12.8	44	14.6	145	Tube Type	175	A5	19,775	15,212
12.00-20	330/95-20	24	8.0-20	45.1	12.8	44	14.6	151	Tube Type	178	A5	21,407	16,469
12.00-20	330/95-20	28	8.0-20	45.1	12.8	44	14.6	158	Tube Type	180	A5	22,928	17,637
12.00-24	330/95-24	20	8.5-24	49.0	12.6	44	14.9	145	Tube Type	178	A5	21,495	16,535
12.00-24	330/95-24	24	8.5-24	49.0	12.6	44	14.9	151	Tube Type	178	A5	21,925	16,865
14.00-24	385/95-24	24	10.00W-24	53.5	15.0	49	17.7	145	Tube Type	186	A5	27,227	20,944
14.00-24	385/95-24	24*	10.00W-24	53.5	15.0	49	17.7	145	Tubeless	186	A5	27,227	20,944
14.00-24	385/95-24	28	10.00W-24	53.5	15.0	49	17.7	151	Tube Type	186	A5	27,778	21,363

* Requires special rim & components. please check with your local Trelleborg representative



Yokohama TWS North America, Inc.
 107 Audubon Road - Building 2 - Suite 205
 Wakefield, MA 01880
 800-948-8473
 info.tws@yokohama-tws.com
 www.trelleborg-tires.com/en-us

Follow us



Subject to technical amendments, printing errors and mistakes in text or illustrations. 09.23