

T-840

Consistent performance



STABILITY



TRACTION



COOL RUNNING

The daily challenge in material handling is to achieve dependable results without compromising efficiency. The Trelleborg T-840 meets this need with a dense tread design that delivers consistent grip and stability in medium-intensity applications.

Its smart tread design ensures precise steering control, giving operators confidence in everyday operations.

T-840

Built for everyday duty

Bias-ply pneumatic tire designed for medium-intensity applications, delivering reliable results across a wide range of operating conditions.

Ideal for forklifts, loaders, and industrial vehicles working in logistics hubs, warehouses, and manufacturing facilities, the T-840 offers a balanced combination of heat resistance, ride comfort, and durability over time.

This makes it suitable for use at speeds up to 35 km/h, supporting efficient long-distance travel in large material handling environments.

1 Block tread design for improved traction

2 Pattern designed to enhance directional stability

3 Shock-absorbing structure for heavy-duty service



T-840

TREAD PATTERN



Size (alternative size)	Type	Rim (permitted)	Section width (mm)	Overall diameter (mm)	Minimal dual spacing (mm)	Tread depth (mm)	Service description LI/SS	Ply rating	Tire load capacity (kg)		Tire pressure (bar)
									Load Wheel	Steering Wheel	
15x4.5-8 (125/75-8)	TT	3.00D-8	117	381	140	8	100 A5	12 PR	1040	800	10.00
4.00-8	TT	3 1 (4I-8)	112	414	138	6	94 A5 97 A5	8 PR 10 PR	870 950	670 730	9.00 10.00
16x6-8 (150/75-8)	TT	4.33R-8	152	425	175	12	113 A5	16 PR	1495	1150	10.00
18x7-8 (180/70-8)	TT	4.33R-8	173	462	199	14	121 A5 125 A5	14 PR 16 PR	1885 2145	1450 1650	9.00 10.00
5.00-8	TT	3.00D-8	132	467	158	11	106 A5 111 A5	8 PR 10 PR	1235 1415	950 1090	8.25 10.00
21x8-9 (200/75-9)	TT	6.00E-9	200	535	230	15	131A5 134 A5	14PR 16 PR	2535 2755	1950 2120	9.00 10.00
6.00-9	TT	4.00E-9	160	540	192	13	118 A5 121 A5	10 PR 12 PR	1715 1885	1320 1450	8.50 10.00
6.50-10	TT	5.00F-10 (5.50F-10)	177	588	212 (218)	14	122 A5 125 A5 128 A5	10 PR 12 PR 14 PR	1950 2145 2340	1500 1650 1800	7.75 9.00 10.00
23x10-12 (250/60-12)	TT	8.00G-12	243	594	293	20	139 A5	16 PR	3160	2430	8.00
23x9-10 (250/75-12)	TT	6.50F-10	225	595	259	16	142 A5	20 PR	3340	2650	10.00
7.50-10	TT	5.00F-10	205	643	242	15	133 A5	12 PR	2680	2060	8.00
7.00-12	TT	5.00S-12	192	672	230	15	133 A5 134 A5 136 A5	12 PR 14 PR 16 PR	2680 2755 2910	2060 2120 2240	8.50 9.00 10.00
27x10-12 (250/75-12)	TT	8.00G-12	261	681	293	18	143 A5 146 A5 152 A5	14 PR 16 PR 20 PR	3545 3900 4615	2725 3000 3550	7.00 8.00 10.00
8.15-15 (28x9-15)	TT	7.0-15	216	707	248	18	146 A5	14 PR	3900	3000	10.00
28x12.5-15	TT	9.75-15	274	728	397	17	151 A5	20 PR	4535	3490	9.00
250-15 (250/70-15)	TT	7.50-15	250	735	288	20	153 A5 155 A5	18 PR 20 PR	4745 5040	3650 3875	9.50 10.00
7.00-15	TT	5.50-15 (6.0-15)	198	748	236 (242)	17	140 A5	14 PR	3250	2500	9.25
7.50-15	TT	6.0-15 (6.5-15)	212	772	254 (260)	21	142 A5 144 A5 146 A5	12 PR 14 PR 16 PR	3445 3640 3900	2650 2800 3000	8.00 9.25 10.00
8.25-15	TT	6.5-15	234	836	281	23	149 A5 153 A5	14PR 18 PR	4225 4745	3250 3650	8.00 10.00
300-15 (315/70-15)	TT	8.00-15	300	840	345	23	164A5 165 A5	20PR 22 PR	6500 6695	5000 5150	9.00 10.00

The information and technical data provided in this catalogue are indicative and may be subject to change without prior notice. For up-to-date data and official product specifications, please refer to the product technical sheet available through your sales representative.



Printed on recycled paper



Shop our tires online



**Discover our website
and your legal guarantee rights**

Follow us

